

UDOT Minimum Sampling and Testing Requirements

Revised April '07

Specification - Material: 02786 Open Graded Surface Course

Assurance: Asphalt Binder Content and Sieve Analysis

Reference: AASHTO T 308 and AASHTO T 30

Lot Size: Production Day

Frequency per Lot: Four samples per production day is standard, for exceptions see Section 02786 "Acceptance."

Point of Acceptance: Hot Plant

Sampling Reference: MOI 8-984

Report/Form:

Assurance: Thickness

Reference: Verify with a depth probe

Lot Size:

Frequency per Lot:

Point of Acceptance:

Sampling Reference:

Report/Form:

Assurance: Smoothness

Reference: Standard Specification 01452

Lot Size:

Frequency per Lot:

Point of Acceptance:

Sampling Reference:

Report/Form:

<i>Specification - Material:</i> 02786 Open Graded Seal Coat

Assurance: Visual Acceptance of very small quantities of materials

Reference: Acceptance is limited to material being furnished from sources found satisfactory under normal sampling and testing procedures.

Lot Size: Not to exceed 100 tons per day or 1000 tons per project

Frequency per Lot: One report for each day material is accepted

Point of Acceptance: Grade

Sampling Reference:

Report/Form: Visual Inspection Report
